

Technical Data Sheet (TDS)

Product Name: PolyetherPAG-320

Product Introduction

PAG-320 polyether is a type of high-performance lubricant base oil polyo synthesized primarily from propylene oxide. The product features lo hygroscopicity, is insoluble in water, and partially soluble in hydrocarbons. I readily adsorbs onto the surface of media, reducing surface tension, an exhibits excellent penetration and lubrication properties. It can be synthesize to produce base oils with specific molecular weights, viscosities, an structures. The product is widely used in industrial air compressor oils various gas compressor oils, industrial gear oils, fire-resistant hydrauli fluids, high-temperature chain oils, and other fields.

Specifications

Item	PAG-320	Test Method
Appearance	Clear liquid, free of suspended matter	Q/ZHDDZB 05.10.001-2024
Water Content, %	≤0.050	Q/ZHDDZB 05.10.001-2024
Potassium Ion, mg/kg	≤5	Q/ZHDDZB 05.10.001-2024
Acid Value, mgKOH/g	≤0.05	Q/ZHDDZB 05.10.001-2024
Color (APHA)	≤50	Q/ZHDDZB 05.10.001-2024
Kinematic Viscosity (40° C), mm ² /s	315 - 325	Q/ZHDDZB 05.10.001-2024
Viscosity Index	≥224	Q/ZHDDZB 05.10.001-2024
Flash Point, ° C	≥225	Q/ZHDDZB 05.10.001-2024
Pour Point, ° C	≤-35	Q/ZHDDZB 05.10.001-2024

Packaging

Packed in clean, dry, sealed, leak-proof dedicated painted iron drums, net weight 200 kg per drum; or in tank trucks, flexitanks, IBCs. Packaging can also be customized according to customer requirements. Containers must be tightly closed.

Storage & Transportation

During transportation of PAG-320, protect from rain and contamination. Handle with care to avoid impact with hard objects that may cause leakage.

Store PAG-320 in a ventilated, dry warehouse at room temperature. Avoid damp environments. Storage temperature should be maintained below 50° C. Avoid direct sunlight and keep away from water sources and heat sources. Alternatively, store sealed in containers made of steel, aluminum, polyethylene, or polypropylene. To prevent moisture absorption and oxidation, it is recommended to fill the container headspace with nitrogen. Storage temperatures above 60° C will lead to product quality degradation. Short-term temperature increases or decreases have little impact on product quality; however, note that the product's viscosity increases significantly at lower temperatures, which may cause difficulties in processing.

Shelf Life

Under correct storage conditions, the shelf life is 1 year from the date of production. The product may still be used after this period if re-inspection confirms it meets specifications.

Note: For low-odor products, customers are advised to use them as soon as possible.

Safety Information

PAG-320 is classified as a non-hazardous substance. It has a high flash point and is combustible. Use foam, dry powder, steam, or water to extinguish fires. It is not explosive. It is practically non-toxic, and no special ventilation is required. The toxicity of typical neutral polyether polyols upon ingestion or contact with skin, eyes, or mucous membranes is negligible. In case of skin contact, wash with soapy water. In case of eye contact, flush with low-pressure clean water or seek medical treatment. Workers may wear eye protection or safety glasses. Eye wash and shower facilities should be available nearby the work area. The product is generally considered non-hazardous to skin. Practice personal hygiene when working in areas where contact with the product is possible. Wash skin that has been in contact with the product using cleaning agents before eating, smoking, or leaving the work area.

Spill Handling

Stop the leak if it is safe to do so. For minor spills, absorb with sand or other absorbent material and place in a clean, dry container for subsequent disposal. For large spills, contain and collect the spilled material for disposal. Prevent the material from entering groundwater or surface water, as it is not readily biodegradable. All collected spill material should be disposed of in accordance with local environmental regulations.

Disclaimer

The information and technical advice provided above are obtained from reliable sources. However, we make no warranty, express or implied, regarding the data provided and give no guarantees herein. We recommend conducting a series of tests before using our product. We are not responsible for the application, use, processing, or production of goods based on the technical information we provide, and such responsibilities lie solely with the user. The conditions and methods of handling, storage, use, or disposal of this product are beyond our control and may be beyond our knowledge. Under no circumstances shall we be liable for any loss, damage, or expenses incurred due to improper handling, storage, use, or disposal of this chemical.

For more information, please refer to the Technical Safety Data Sheet (SDS) of our product or contact our Market Service Department.

Contact Information

Sinochem Dongda (Zibo) Co., Ltd.

Address: No. 25888 North Waihuan Road, Huantai County, Shandong Province, China

Tel: 0086-0533-7878333

E-mail: dongda@sinochem.com

Website: <http://www.lxdd.chemchina.com/>

Postal Code: 256405