

# Product Technical Data Sheet (TDS)

Polyether A-1100E - Bisphenol A Series Polyoxyethylene Ether

## Product Introduction

A-1100E is a bisphenol A series polyoxyethylene ether, suitable for the preparation of polyurethane adhesives, elastomers, and coatings. When applied in adhesives, coatings, dry films, and lenses, it can improve the mechanical strength of coatings, enhance aging resistance, and possesses good chemical corrosion resistance and electrical properties. UV adhesives prepared with this product exhibit excellent bonding performance and photosensitive characteristics, enabling rapid curing under ultraviolet irradiation and improving overall impact resistance.

## Product Specifications

| Item                    | A-1100E                                             | Test Standard           |
|-------------------------|-----------------------------------------------------|-------------------------|
| Appearance              | Clear liquid, free of suspended matter (above 80°C) | Q/ZHDDZB 05.10.001-2024 |
| Water Content, %        | ≤0.05                                               | Q/ZHDDZB 05.10.001-2024 |
| Potassium, mg/kg        | ≤5                                                  | Q/ZHDDZB 05.10.001-2024 |
| pH Value                | 5.0-7.2                                             | Q/ZHDDZB 05.10.001-2024 |
| Hydroxyl Value, mgKOH/g | 101±5                                               | Q/ZHDDZB 05.10.001-2024 |
| Acid Value, mgKOH/g     | ≤0.05                                               | Q/ZHDDZB 05.10.001-2024 |
| Color (APHA)            | ≤50 (above 80°C)                                    | Q/ZHDDZB 05.10.001-2024 |
| Viscosity mPa·s (25°C)  | 760-900                                             | Q/ZHDDZB 05.10.001-2024 |

## Packaging

Packaged in clean, dry, sealed, leak-proof special painted iron drums, net weight 200kg per drum; or in tank trucks, flexitanks, IBCs. Can also be packaged according to customer requirements. Packaging containers must be tightly closed.

## Storage & Transportation

---

During transportation of A-1100E, protect against rain and contamination. Handle with care, avoid collision with hard objects to prevent leakage.

A-1100E should be stored in a ventilated, dry warehouse at room temperature. Avoid damp environments. Storage temperature should be kept below 50°C. Avoid direct sunlight. Keep away from water sources and heat sources. Alternatively, store sealed in containers made of steel, aluminum, polyethylene, or polypropylene. To prevent moisture absorption and oxidation, it is recommended to fill the container with nitrogen gas. Storage temperatures above 60°C will lead to product quality degradation. Short-term temperature increases or decreases have little effect on product quality, but note that viscosity increases significantly at lower temperatures, which may cause some difficulties in production and processing.

## Shelf Life

---

Under correct storage conditions, the shelf life is 1 year from the date of production.

Note: For low-odor products, customers are advised to use them as soon as possible.

## Safety Information

---

A-1100E is classified as a non-hazardous substance. It has a high flash point and is combustible. In case of fire, use foam, dry powder, steam, or water to extinguish. It is not explosive. It is almost non-toxic and requires no special ventilation. The toxicity of generally neutral polyether polyols upon ingestion or contact with skin, eyes, or mucous membranes is considered negligible. In case of skin contamination, wash with soapy water. In case of eye contact, flush with low-pressure clean water or seek medical treatment. Workers can wear protective goggles or safety glasses to protect their eyes. Eye wash and shower equipment should be available near the workplace. The product is generally considered non-hazardous to skin. When working in areas where contact with the product is possible, pay attention to personal hygiene. Before eating, smoking, or leaving the work area, clean skin that has been in contact with the product using cleaning products.

## Spill Handling

---

Stop the leak if it is safe to do so. For minor spills, absorb with sand or other absorbent material and place in a clean, dry container for subsequent disposal. For large spills, contain the spilled material for subsequent recovery. Prevent material from entering groundwater or surface water, as it is not readily biodegradable. All collected spill material should be disposed of according to local environmental regulations.

## Disclaimer

---

The information and technical advice provided above are obtained from reliable sources. However, we make no express or implied warranties regarding the provided data and offer no guarantees herein. We recommend conducting a series of tests if you intend to use our product. The application, use, processing, or production of products based on the technical information we provide is beyond our control, and therefore the responsibility lies with the user. The conditions and methods for handling, storage, use, or disposal of this product are beyond our control and may exceed our knowledge. In no event shall we be liable for any losses, damages, or expenses incurred due to improper handling, storage, use, or disposal of this chemical.

For more information, please refer to the Technical Safety Data Sheet (SDS) of our product or contact our Market Service Department.

## Contact Information

---

**Sinochem Dongda (Zibo) Co., Ltd.**

Address: Huantai Maqiao Chemical Industry Park, Zibo City, Shandong Province, China

Tel: 0086-0533-7878333

E-mail: [dongda@sinochem.com](mailto:dongda@sinochem.com)

Website: <http://www.lxdd.chemchina.com/>

Postal Code: 256405

[Download as PDF](#)